



ГЕНЕРАТОРЫ УПРАВЛЯЕМЫЕ НАПРЯЖЕНИЕМ (кристаллы)

ГУН

Type \ Parameter	Frequency range (GHz)	Tuning voltage (V)	Pout (dBm)	SSB phase noise@10KHz (dBc)	Second harmonic suppression (dBc)	Push frequency coefficient (MHz/V)	Power dissipation (V/mA)
NC1405C-2629	2.6-2.9	0-12	6.5*	-86*	-7*	18*	3/41
NC1406C-2933	2.9-3.3	0-12	7.3*	-86*	-7*	18*	3/44
NC1407C-3336	3.3-3.6	0-12	8*	-85*	-8*	18*	3/45
NC1408C-3539	3.5-3.9	0-12	7.5*	-83*	-8*	18*	3/48
NC1409C-4045	4.0-4.5	0-8	4.2*	-78*	-8*	18*	3/42
NC1411C-4550	4.5-5.0	0-8	3*	-80*	-7*	18*	3/39
NC1412C-5056	5.0-5.6	0-8	5*	-78*	-14*	18*	3/40
NC1413C-5561	5.5-6.1	0-8	5*	-76*	-13*	18*	3/41

Note: *: Typical specification; All chips above could be provided by the modality of in packages or modules.